

Certificate No. **MATS/2669/2**

This certificate is issued to the company named below. The ballast tank maintenance coating described has been recognised for use in constructions built under Lloyd's Register survey. This recognition is subject to Lloyd's Register being informed of any changes in or modifications to the coating and the product being used in accordance with the manufacturer's instructions and with the relevant requirements of Lloyd's Register's Rules and Regulations.

Company	<b>NORTRADE AS KRISTIANSAND NORWAY</b>
Trade name	<b>ACTIVE RUST PRIMER 662 SG</b>
Class	<b>CLASS 2</b>
Coating Type	<b>CONVERSION</b>
Number of Coats	<b>2</b>
Coating Thickness	<b>100-120 microns</b>
Remarks	<b>1. As this is a rust converting primer, for tank maintenance purposes it must be used with an epoxy corrosion control coating. 2. The system is a Class 2 maintenance coating being subject to annual inspections until suitably coated tanks, which have been in service for a period of not less than 3 years, have been examined by LR's Surveyors and found to be satisfactory. Endorsement: As the system comprises Active Rust Primer 662 SG and epoxy corrosion control coatings, users should confirm the suitability/compatibility of the respective coating materials.</b>

Valid until **14 August 2013**Date **18 August 2008****R Dawson**Surveyor to Lloyd's Register EMEA  
A member of the Lloyd's Register  
Group